




Bearing Designation			Shaft Diameter(mm)	Weight(Kg)	Boundary Dimensions(mm)					Basic Load Rating(N)		Limiting Speed(rpm) Oil
Without IR	Weight	With IR			d	Fw	D	C	B	Dynamic	Static	
RNA4920	1006	-	-	115	-	115	140	-	40	120000	264000	3700
RNA4922	1200	-	-	125	-	125	150	-	40	124000	270000	3300
RNA4924	1760	-	-	135	-	135	165	-	45	174000	386000	2900
RNA4928	2350	-	-	160	-	160	190	-	50	200000	460000	2900
RNA6919	1325	-	-	110	-	110	130	-	63	196000	400000	3870
RNA4919	685	-	-	110	-	110	130	-	35	112000	245000	3870
RNA6918	1250	-	-	105	-	105	125	-	63	174000	38000	4000
RNA4918	713	-	-	105	-	105	125	-	35	98500	239000	4000
RNA6917	1112	-	-	100	-	100	120	-	63	161000	337000	4600
RNA4917	608	-	-	100	-	100	120	-	35	98000	207000	4600
RNA6916	978	-	-	90	-	90	110	-	54	130500	280600	5000
RNA4916	496	-	-	90	-	90	110	-	30	81000	170500	5000
RNA6X13X8TN	-	-	-	90	-	6	13	-	8	-	-	-
RNA22010 2RSX	563	NA22010 2RSX	690	90	50	58	90	23	22.7	66000	86000	1300
RNA22010 2RS	563	NA22010 2RS	690	90	50	58	90	23	22.7	66000	86000	1300
RNA6915	923	-	-	85	-	85	105	-	54	128000	272000	5500
RNA5915	745	-	-	85	-	85	105	-	40	-	-	-
RNA4915	472	-	-	85	-	85	105	-	30	82000	158000	5500
RNA2209 2RSX	545	NA2209 2RSX	655	85	45	52	85	23	22.7	40300	63800	1600
RNA2209 2RS	545	NA2209 2RS	655	85	45	52	85	23	22.7	40300	63800	1600
RNA6914	815	-	-	80	-	80	100	-	54	121000	263000	5500
RNA4914	400	-	-	80	-	80	100	-	30	79000	154000	5500
RNA2208 2RSX	530	NA2208 2RSX	628	80	40	48	80	23	22.7	38200	57700	1700
RNA2208 2RS	530	NA2208 2RS	628	80	40	48	80	23	22.7	38200	57700	1700
RNA6913	571	-	-	72	-	72	90	-	45	87600	194500	6500
RNA4913	300	-	-	72	-	72	90	-	25	57500	110500	6500
RNA2207 2RSX	432	NA2207 2RSX	505	72	35	42	72	23	22.7	29800	46300	2200
RNA2207 2RS	432	NA2207 2RS	505	72	35	42	72	23	22.7	29800	46300	2200

RNA6912	436	-	-	68	-	68	85	-	45	88500	186000	7000
RNA5912	408	-	-	68	-	68	85	-	34	-	-	-