



|                                     |           |
|-------------------------------------|-----------|
| Designation :                       | 30311J2/Q |
| Principal dimensions(mm)            |           |
| d1 :                                | 55        |
| D :                                 | 120       |
| B :                                 | 31,5      |
| Basic load ratings(KN)              |           |
| dyc(Cr) :                           | 166       |
| stc(Cor) :                          | 163       |
| Pu :                                | 19,3      |
| Speed ratings(rpm)                  |           |
| Speed Ratings :                     | 4800      |
| Limiting Speed :                    | 5600      |
| Weight(Kg) :                        | 1,55      |
| ISO335                              |           |
| Dimensions (ABMA) :                 | 2FB       |
| Dimensions (mm)                     |           |
| d :                                 | 55        |
| d1□ :                               | 84        |
| B :                                 | 29        |
| C :                                 | 25        |
| r1,2(min) :                         | 2,5       |
| r3,4(min) :                         | 2         |
| a :                                 | 24        |
| Abutment and fillet dimensions (mm) |           |
| da(max) :                           | 71        |
| db(min) :                           | 65        |
| Da(min) :                           | 104       |
| Da(max) :                           | 112       |
| Db(min) :                           | 111       |
| Ca(min) :                           | 4         |
| Cb(min) :                           | 6,5       |
| ra(max) :                           | 2         |
| rb(max) :                           | 2         |
| Value                               |           |
| e :                                 | 0,35      |
| Y :                                 | 1,7       |
| Yo :                                | 0,9       |