



|                                |          |
|--------------------------------|----------|
| Type :                         | SBG65FL  |
| Mounting Dimensions            |          |
| Height(H) :                    | 90       |
| E :                            | 17.5     |
| W2 :                           | 53.5     |
| Width(W) :                     | 170      |
| Length(L) :                    | 186      |
| Block Dimensions               |          |
| Mounting tab hole(B×J) :       | 142*110  |
| Mounting tab hole(M×L) :       | M16*24   |
| L1 :                           | 147      |
| J1 :                           | 18.5     |
| K :                            | 72.5     |
| T :                            | 23       |
| Nipple Mounting Hole :         | PT1/8    |
| Nipple(T1) :                   | 15       |
| Nipple(N) :                    | 16       |
| Rail Size                      |          |
| Width(W1) :                    | 63       |
| Height(H1) :                   | 58.5     |
| Pitch(F) :                     | 150      |
| Bolt Hole(d×D×h) :             | 18*26*22 |
| G :                            | 35       |
| Max.length Of rail Lomax :     | 4390     |
| Load capacity                  |          |
| Dynamic C(kgf) :               | 14380    |
| Sationary Co(kgf) :            | 21900    |
| Stationary moment(kgf.M) MRO : | 629      |
| Stationary moment(kgf.M) MPO : | 493      |
| Stationary moment(kgf.M) MRO : | 484      |
| Weight                         |          |
| bearing (kgf) :                | 6.24     |
| rail (kgf/M) :                 | 21.3     |